



Brand: BendPak
Model: HD-9SW / HD-9SWX
Description: Double-Wide Four-Post Lift

- 9,000 Pound Lifting Capacity
- Double-Wide Configuration For Quad Vehicle Storage
- Two Models To Choose / Short Standard Rise / Long Tall Rise
- Runways Include Rail-Kit For Optional Accessories
- Electric/Hydraulic Power System
- Single Hydraulic Cylinder Mounted Underneath Runway
- Internal "Anti-Sway" Slider Blocks In Each Column
- Features Heavy-Duty 3/8" Aircraft Cable
- Oversized Self-Lubricating Cable Rollers
- Rugged 1-1/4" Roller Axles
- Multi-Position Safety Locks In Each Column
- Ramps Feature Non-Skid Surface
- Push-Button Safety Release
- Inside Runways Adjust For Different Tread Widths



MODEL	HD-9SW	HD-9SWX
Lifting Capacity*	9,000 lbs. / 4082 kg.	9,000 lbs. / 4082 kg.
*Max Capacity / Front Axle	4,500 lbs. / 2041 kg.	4,500 lbs. / 2041 kg.
*Max Capacity / Rear Axle	4,500 lbs. / 2041 kg.	4,500 lbs. / 2041 kg.
A - Overall Width	206" / 5232 mm.	206" / 5232 mm.
B - Outside Length	174" / 4420 mm.	198" / 5029 mm.
C - Overall Length	200" / 5080 mm.	224" / 5690 mm.
D - Height of Columns	88" / 2235 mm.	100" / 2540 mm.
E - Min. Runway Height	7" / 178 mm.	7" / 178 mm.
F - Max. Rise	70" / 1778 mm.	82" / 2083 mm.
G - Max. Lifting Height	77" / 1956 mm.	89" / 2261 mm.
H - Width Between Columns	192" / 4877 mm.	192" / 4877 mm.
I - Runway Width	19" / 483 mm.	19" / 483 mm.
J - Width Between Runways (*)	37" - 42" / 940 mm. - 1067 mm.	37" - 42" / 940 mm. - 1067 mm.
K - Length of Runways	164" / 4166 mm.	188" / 4775 mm.
Min. Wheelbase @ Rated Capacity	115" / 2921 mm.	135" / 3429 mm.
Min. Wheelbase @ 75% Capacity	100" / 2540 mm.	115" / 2921 mm.
Min. Wheelbase @ 50% Capacity	85" / 2159 mm.	95" / 2413 mm.
Min. Wheelbase @ 25% Capacity	70" / 1778 mm.	80" / 2032 mm.
L - Outside Column Spacing	15-1/2" / 394"	15-1/2" / 394"
Locking Positions	14	16
Lock Spacing	Every 4" / 102 mm.	Every 4" / 102 mm.
Lifting Time	55 Seconds	65 Seconds
Standard Motor (**)	220 VAC / 60 Hz. 1Ph.	220 VAC / 60 Hz. 1Ph.
* This dimension may be limited with the addition of rolling jacks or drip-trays. See option specifications on separate page(s).		
** Special Voltages Available Upon Request		
The design, material and specifications are subject to change without notice.		



FLOORPLAN(S)

MODEL	HD-9SW	HD-9SWX
A - Overall Width	206" / 5232 mm.	206" / 5232 mm.
B - Outside Length	174" / 4420 mm.	198" / 5029 mm.
C - Overall Length	200" / 5080 mm.	224" / 5690 mm.
D - Height of Columns	88" / 2235 mm.	100" / 2540 mm.
E - Min. Runway Height	7" / 178 mm.	7" / 178 mm.
F - Max. Rise	70" / 1778 mm.	82" / 2083 mm.
G - Max. Lifting Height	77" / 1956 mm.	89" / 2261 mm.
H - Width Between Columns	192" / 4877 mm.	192" / 4877 mm.
I - Runway Width	19" / 483 mm.	19" / 483 mm.
J - Width Between Runways (*)	37" - 42" / 940 mm. - 1067 mm.	37" - 42" / 940 mm. - 1067 mm.
K - Length of Runways	164" / 4166 mm.	188" / 4775 mm.
L - Outside Column Spacing	15-1/2" / 394"	15-1/2" / 394"
* This dimension may be limited with the addition of rolling jacks or drip-trays. See option specifications on separate page(s).		
** Special Voltages Available Upon Request		
The design, material and specifications are subject to change without notice.		

