



Brand: BendPak
Model: XPR-7TR / XPR-7RFX
Description: Turf Lifts

BendPak's XPR-7TR and XPR-7TRFX turf lifts are the most versatile lawn maintenance and utility vehicle lifts on the market – all backed by a service and support excellence that only BendPak's 40-year experience can provide. These fully equipped turf lifts greatly increase speed and maintenance repair work on all popular sizes of turf maintenance equipment ranging from large fairway mowers to greens mowers, utility carts, sand groomers, fertilizer sprayers, golf and refreshment carts. Fully adjustable full-width wheel pan and fork assemblies fit a wide array of equipment wheel configurations and help provide open access to the hydraulics, blades, reels and other components for increased shop efficiency. The XPR-7TRFX is an open-top, floor-pan model and the XPR-7TR is a clear-floor model with overhead beam.

- The XPR-7TRFX is configured from our ETL Certified XPR-9FDX two-post lift.
- The XPR-7TR is configured from our ETL Certified XPR-10CX two-post lift.
- 7,000-pound capacity
- Wide drive thru
- Single piece columns
- Single point safety release
- Dual hydraulic "Direct-Drive" cylinders
- Electric/hydraulic power system
- Large, 19" x 17" steel base plates
- Self-lubricating dura-glide polyethylene bearing system
- Safety locks in each column spaced every 3-inches
- Fully adjustable full-width wheel pan and fork assemblies
- to accommodate a wide variety of vehicle wheelbases
- Full-width wheel pan ideal for single or dual rear wheeled vehicles
- Heavy-duty dual 3/8" equalizer cables with oversize sheaves
- Padded overhead safety-shutoff bar



XPR-7TRFX
Open-Top Floor-Pan Model



XPR-7TR
Clear-Floor Model

NOTE: Turf attachments can be easily removed and replaced with standard swing arm assemblies (purchased separately) to convert for regular automotive and light truck service.

MODEL	XPR-7TRFX	XPR-7TR
Lifting Capacity	7,000 Lbs. / 3175 Kg.	7,000 Lbs. / 3175 Kg.
- Max Load / Wheel Pan:	3,500 Lbs. / 1588 Kg.	3,500 Lbs. / 1588 Kg.
- Max Load Per Fork:	1,750 Lbs. / 794 Kg.	1,750 Lbs. / 794 Kg.
Height Overall: (*)	145" / 3683 mm.	145" / 3683 mm.
Width Overall (Outside of Base Plate):	145" / 3683 mm.	145" / 3683 mm.
Width (Outside of Columns):	137" / 3480 mm.	137" / 3480 mm.
Floor To Overhead Switch-XPR-7TR: (*)	141" / 3581 mm.	141" / 3581 mm.
Inside Columns:	115" / 2921 mm.	115" / 2921 mm.
Rise:	69" / 1753 mm.	69" / 1753 mm.
Drive-Thru Clearance:	106" / 2692 mm.	106" / 2692 mm.
Motor (**)	220 VAC / 60 Hz. 1Ph.	220 VAC / 60 Hz. 1Ph.
Time of full Rise:	45 Seconds	45 Seconds

* An optional bolt-on top extension can be added to the XPR-7TR that raises the overhead bar an additional 24". Must be ordered from factory at time of order.

** Special Voltages Available Upon Request.
The design, material and specifications are subject to change without notice.